HIPRAULIC TOOLS

JCS - COMPACT JACKS - SOLID PISTON



Capacities from 10 to 30 tonnes	
Operates in any position	

Lightweight and compact

The Hi-Force JCS range of compact jacks is ideally suited for applications requiring a lifting or positioning force in confined spaces. Lightweight, easy to operate and manufactured from high grade steel (JCS10) and aluminium (JCS20 & JCS30), all models incorporate a spring assisted return, wear coated piston. The pumping mechanism rotates through 360° providing maximum versatility in any application. With the removable operating handle measuring only 240mm in length, these compact lifting jacks will fit in any toolbox.

- >> Spring assisted return piston
- >> Multi-position pump mechanism

Steel

Aluminium

Aluminium

>> Internal safety overload valve

number tonnes Material

10

20

30

Model Capacity

JCS10

JCS20

JCS30

>>	Nitrocarburised	piston	rod
----	-----------------	--------	-----

>> Sealed hydraulic system

		Dimensions in mm					
Stroke	Weight		Closed		Max		
mm	kg	Length	Height	Piston Dia.	handle height	Width	
35	4.5	240	76	38	266	70	
41	5.5	257	102	51	281	102	
45	8.0	281	112	60	285	125	

JCH - COMPACT JACKS - HOLLOW PISTON



Capacity of 13 and 21 tonnes
Operates in any position
Lightweight and compact

The JCH range of compact jacks is of similar design to the JCS range detailed above, however JCH models feature a hollow piston design for even greater versatility. Suitable for use in tooling, maintenance and tensioning applications, where a pulling force is required. With many common parts to the JCS range these multi-purpose JCH jacks can also be used for general lifting applications.

					Dimensions in mm					
Model Capacity			Stroke Weight			Closed		Max Centre		
number	tonnes	Material	mm	kg	Length	Height	Piston Dia.	handle height	Hole	Width
JCH13	13	Aluminium	41	5.5	257	95	51	281	25	102
JCH21	21	Aluminium	45	8.0	281	114	60	285	35	125